



Light Tower

It suitable for outdoor lighting in power, fire. railway, municipal and other industries. as well as all kinds of outdoor construction operations, accident treatment, emergency rescue and relief. maintenance and emergency repair and so on for mobile lighting and emergency lighting.





101

Light Tower

Light Tower



Model	SFW6110B
The type of light	Halogen lamps
Rated power	4×500W
Luminous flow	9500Lm
Irradiation range	The lighting coverage radius can reach 50~150 meters
Light source life	Tungsten halogen lamp: ≥ 1 year
Angle of rotation of the lamp head	Horizontal 360° adjustable Vertical 90° adjustable
Light tray size	410×330×300mm (4×500W Lamp panel)
Light plate weight	8kg
LIFTING MAST	
Lifting method	Pneumatic adjustable
Lifting height	4.5M/6M(OPTINAL)
Storage height	1.5m/1.8m
Rise time	45S
Descent time	35S
Lift bar weight	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	760mm×450mm×1900mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	60Kg~150Kg

● SFW6110B
All - directional automatic
lifting working light



Model	MF961
The type of light	Halogen lamps
Rated power	4×500W
Luminous flow	9500Lm
Irradiation range	The lighting coverage radius can reach 50~150 meters
Light source life	Tungsten halogen lamp: ≥ 1 year
Angle of rotation of the lamp head	Horizontal 360° adjustable Vertical 90° adjustable
Light tray size	660×120×550mm (4×500W Lamp panel) 800×300×280mm (4×1000W Lamp panel)
Light plate weight	6kg/8kg
LIFTING MAST	
Lifting method	Pneumatic adjustable
Lifting height	4.5M/6M(OPTINAL)
Storage height	1.5m/1.8m
Rise time	45S
Descent time	35S
Lift bar weight	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	760mm×450mm×1900mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	60Kg~150Kg


- ◎ SMF961
Remote control lifting
mobile lighting vehicle



Light Tower

● SMF962A

Manual Lifting Mobile
Lifting Work Light



MODEL	SMF962A
LIGHT TYPE	Halogen lamp 4×500W
LUMINOUS FLUX	9500Lm
RADIATION RANGE	The coverage radius can reach 50 ~ 150 meters
LIGHT OPERATION LIFE	GOLD HALOGEN LAMP:≥1 YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	660×120×550mm (4×500W Lamp panel)
WEIGHT OF LAMP PANEL	6kg/8kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	3M
CLOSED LENGTH	1.2m
LIFTING ROD MATERIAL	stainless steel
LIFTING ROD WEIGHT	3kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	manual control
SHIPPING DIMENSION	640mm×450mm×1500mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	60Kg~150Kg

MODEL	SMF962 LED
LIGHT TYPE	LED 4×100W
LUMINOUS FLUX	12000Lm
RADIATION RANGE	The coverage radius can reach 50 ~ 150 meters
LIGHT OPERATION LIFE	≥1 YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	540×460×60mm (4×100W Lamp panel)
WEIGHT OF LAMP PANEL	6kg/8kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	3M
CLOSED LENGTH	1.2m
LIFTING ROD MATERIAL	stainless steel
LIFTING ROD WEIGHT	3kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	manual control
SHIPPING DIMENSION	640mm×450mm×1500mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	60Kg~150Kg




● SMF962 LED

LEDManual lift mobile
work light

◎ SMF962B

Hand lift moving
work light



MODEL	SMF962B
LIGHT TYPE 1	Halogen lamp 4×500W/4×1000W
LIGHT TYPE 2	LED 4×100W 4×100W/4×200W
RADIATION RANGE	The coverage radius can reach 50 ~ 150 meters
LIGHT OPERATION LIFE	≥1 YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	660×120×550mm (4×500W Lamp panel) 800×300×280mm (4×1000W Lamp panel)
WEIGHT OF LAMP PANEL	6kg/8kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	4.5M
CLOSED LENGTH	1.65m
LIFTING ROD WEIGHT	6kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	manual control
SHIPPING DIMENSION	640mm×450mm×1900mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	60Kg~150Kg

MODEL	SMF963
LIGHT TYPE	Metal halide lamps
RATED POWER	2×400W/2×1000W
LUMINOUS FLUX	2×36000Lm/2×105000Lm
RADIATION RANGE	The coverage radius can reach 100~200meters
LIGHT OPERATION LIFE	≥1 YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	800×430×370mm (2×400WLamp panel) 800×650×550mm (2×1000WLamp panel)
WEIGHT OF LAMP PANEL	8kg/12kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	4.5M/6M(OPTINAL)
CLOSED LENGTH	1.5m/1.8m
RISE TIME	45S
FALL TIME	35S
LIFTING ROD WEIGHT	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	760mm×450mm×1900mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	60Kg~150Kg

◎ SMF963

Remote lift mobile
lighting car



Light Tower

● SMF963B
Hand lift moving
lift work light




MODEL	SMF963B
LIGHT TYPE	Metal halide lamps
RATED POWER	2×400W/2×1000W
LUMINOUS FLUX	2×36000Lm/2×105000Lm
RADIATION RANGE	The coverage radius can reach 100~200meters
LIGHT OPERATION LIFE	≥1 YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	800×430×370mm (2×400WLamp panel) 800×650×550mm (2×1000WLamp panel)
WEIGHT OF LAMP PANEL	8kg/12kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	4.5M/6M(OPTINAL)
CLOSED LENGTH	1.5m/1.8m
LIFTING ROD WEIGHT	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	manual control
SHIPPING DIMENSION	640mm×450mm×1900mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	60Kg~150Kg

MODEL	SMF965
LIGHT TYPE	LED
RATED POWER	4×100W/4×200W
LUMINOUS FLUX	4×10000Lm/4×20000Lm
RADIATION RANGE	The coverage radius can reach 50~150meters
LIGHT OPERATION LIFE	LED:≥3YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	660×70×550mm(4×100WLamp panel) 800×80×820mm (4×200WLamp panel)
WEIGHT OF LAMP PANEL	7kg/10kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	4.5M/6M(OPTINAL)
CLOSED LENGTH	1.5m/1.8m
RISE TIME	45S
FALL TIME	35S
LIFTING ROD WEIGHT	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	760mm×450mm×1900mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	65Kg~150Kg

● SMF965
LED mobile lift
lighting car





● SMF967
Moving spherical
moon lights

MODEL	SMF967
LIGHT TYPE	Metal halide lamps
RATED POWER	1×1000W/2×1000W
LUMINOUS FLUX	1×105000Lm/2×105000Lm
RADIATION RANGE	The coverage radius can reach100~200meters
LIGHT OPERATION LIFE	≥1YEAR
ROTATION ANGLE OF LIGHT	360°
LIGHT PLATE SIZE	Φ1000×800mm(Size of expansion) Φ300×800mm (Size of storage)
WEIGHT OF LAMP PANEL	10kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	4.5M/6M(OPTINAL)
CLOSED LENGTH	1.5m/1.8m
RISE TIME	45S
FALL TIME	35S
LIFTING ROD WEIGHT	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	760mm×450mm×1900mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	80Kg~150Kg

MODEL	SMF967B
LIGHT TYPE1	Metal halide lamps1000W
LIGHT TYPE1	LED 300W 400W 500W
LUMINOUS FLUX	105000Lm/30000Lm
RADIATION RANGE	The coverage radius can reach100~200meters
LIGHT OPERATION LIFE	≥1YEAR
ROTATION ANGLE OF LIGHT	360°
LIGHT PLATE SIZE	Φ1000×800mm(Size of expansion) Φ300×800mm (Size of storage)
WEIGHT OF LAMP PANEL	10kg
LIFTING MAST	
LIFTING METHOD	Hand lift and drop
LIGHTHOUSE TELESCOPIC	4.5M
CLOSED LENGTH	1.5m/1.8m
LIFTING ROD WEIGHT	6kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	640mm×450mm×1900mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	80Kg~150Kg

● SMF967B
Hand lift moving
spherical moon
lamp



Light Tower



◎ SMF951-Q
Automatic lifting
mobile lighting car

MODEL	SMF951-Q
LIGHT TYPE	Halogen lamp
RATED POWER	4×500W/4×1000W
LUMINOUS FLUX	4×9500Lm/4×20000Lm
RADIATION RANGE	The coverage radius can reach 50~150meters
LIGHT OPERATION LIFE	≥1YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	660×120×550mm(4×500W Lamp panel) 800×300×280mm (4×1000W Lamp panel)
WEIGHT OF LAMP PANEL	6kg/8kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	4.5M/6M(OPTINAL)
CLOSED LENGTH	1.5m/1.8m
RISE TIME	45S
FALL TIME	35S
LIFTING ROD WEIGHT	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg

MODEL	SMF953-Q
LIGHT TYPE	Metal halide lamps
RATED POWER	2×400W/2×1000W
LUMINOUS FLUX	2×36000Lm/2×105000Lm
RADIATION RANGE	The coverage radius can reach 100~200meters
LIGHT OPERATION LIFE	≥1YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	800×430×370mm(2×400W Lamp panel) 800×650×550mm (2×1000W Lamp panel)
WEIGHT OF LAMP PANEL	8kg/12kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	4.5M/6M(OPTINAL)
CLOSED LENGTH	1.5m/1.8m
RISE TIME	45S
FALL TIME	35S
LIFTING ROD WEIGHT	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg



◎ SMF953-Q
Automatic lifting
mobile lighting car



SMF955-Q
Automatic lifting LED
mobile lighting car

MODEL	SMF955-Q
LIGHT TYPE	LED
RATED POWER	4×100W/4×200W
LUMINOUS FLUX	4×10000Lm/4×20000Lm
RADIATION RANGE	The coverage radius can reach 50~150meters
LIGHT OPERATION LIFE	≥3YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	660×70×550mm(4×100W Lamp panel) 800×80×820mm(4×200W Lamp panel)
WEIGHT OF LAMP PANEL	7kg/10kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	4.5M/6M(OPTINAL)
CLOSED LENGTH	1.5m/1.8m
RISE TIME	45S
FALL TIME	35S
LIFTING ROD WEIGHT	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg

MODEL	SMF957-Q
LIGHT TYPE	Metal halide lamps
RATED POWER	1×1000W/2×1000W
LUMINOUS FLUX	1×105000Lm/2×105000Lm
RADIATION RANGE	The coverage radius can reach 100~200meters
LIGHT OPERATION LIFE	≥1YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	Φ1000×800mm(Size of expansion) Φ300×800mm(Size of storage)
WEIGHT OF LAMP PANEL	10kg
LIFTING MAST	
LIFTING METHOD	Pneumatic adjustable
LIGHTHOUSE TELESCOPIC	4.5M/6M(OPTINAL)
CLOSED LENGTH	1.5m/1.8m
RISE TIME	45S
FALL TIME	35S
LIFTING ROD WEIGHT	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	8
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg

● **SMF957-Q**
Automatic lift moving
spherical moon lamp



Light Tower



● SMF951-S
Hand lift mobile
lighting car

MODEL	SMF951-S
LIGHT TYPE	halide lamps
RATED POWER	4×500W/4×1000W
LUMINOUS FLUX	4×9500Lm/4×20000Lm
RADIATION RANGE	The coverage radius can reach100~200meters
LIGHT OPERATION LIFE	≥1YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	660×120×550mm (4×500W Lamp panel) 800×300×280mm (4×1000W Lamp panel)
WEIGHT OF LAMP PANEL	6kg/8kg
LIFTING MAST	
LIFTING METHOD	Hand lift and drop
LIGHTHOUSE TELESCOPIC	4.5M
CLOSED LENGTH	1.6m
RISE TIME	1600mm×360mm×180mm
FALL TIME	30kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg

MODEL	SMF953-S
LIGHT TYPE	Metal halide lamps
RATED POWER	2×400W/2×1000W
LUMINOUS FLUX	2×36000Lm/2×105000Lm
RADIATION RANGE	The coverage radius can reach100~200meters
LIGHT OPERATION LIFE	≥1YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	800×430×370mm(2×400W Lamp panel) 800×650×550mm(2×1000W Lamp panel)
WEIGHT OF LAMP PANEL	8kg/12kg
LIFTING MAST	
LIFTING METHOD	Hand lift and drop
LIGHTHOUSE TELESCOPIC	4.5M
CLOSED LENGTH	1.6m
RISE TIME	1600mm×360mm×180mm
FALL TIME	30kg
LIFTING ROD WEIGHT	6kg/12kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg



● SMF953-S
Hand lift mobile
lighting car


◎ SMF952-S
Hand lift mobile
lighting car



MODEL	SMF952-S
LIGHT TYPE	LED
RATED POWER	4×750W
LUMINOUS FLUX	4×75000Lm
RADIATION RANGE	The coverage radius can reach 50~150meters
LIGHT OPERATION LIFE	≥1YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	900×120×900mm
WEIGHT OF LAMP PANEL	6kg/8kg
LIFTING MAST	
LIFTING METHOD	Hand lift and drop
LIGHTHOUSE TELESCOPIC	4.5M
CLOSED LENGTH	1.6m
SIZE OF PACKAGE	1600mm×360mm×180mm
LIFTING ROD WEIGHT	30kg
LIFTING ROD WEIGHT	6kg/12kg
GENERATOR	
ENGINE TYPE	diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	6KW
STARTING SYSTEM	electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg

MODEL	SHMF952-Q
LIGHT TYPE	LIGHT TYPE
RATED POWER	RATED POWER
LUMINOUS FLUX	LUMINOUS FLUX
RADIATION RANGE	RADIATION RANGE
LIGHT OPERATION LIFE	LIGHT OPERATION LIFE
ROTATION ANGLE OF LIGHT	ROTATION ANGLE OF LIGHT
LIGHT PLATE SIZE	LIGHT PLATE SIZE
WEIGHT OF LAMP PANEL	WEIGHT OF LAMP PANEL
LIFTING MAST	
LIFTING METHOD	Automatic lifting and lowering
LIGHTHOUSE TELESCOPIC	4.5M
CLOSED LENGTH	1.6m
SIZE OF PACKAGE	1600mm×360mm×180mm
LIFTING ROD WEIGHT	8kg
GENERATOR	
ENGINE TYPE	diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	6KW
STARTING SYSTEM	electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg

◎ SHMF952-Q
Automatic lifting
mobile lighting car



Light Tower



◎ SMF955-S
Hand-lift LED
mobile lighting car

MODEL	SMF955-S
LIGHT TYPE	LED
RATED POWER	4×100W/4×200W
LUMINOUS FLUX	4×10000Lm/4×20000Lm
RADIATION RANGE	The coverage radius can reach 50~150meters
LIGHT OPERATION LIFE	LED: ≥3YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	660×70×550mm (×100W Lamp panel) 800×80×820mm (4×200W Lamp panel)
WEIGHT OF LAMP PANEL	7kg/10kg
LIFTING MAST	
LIFTING METHOD	Hand lift and drop
LIGHTHOUSE TELESCOPIC	4.5M
CLOSED LENGTH	1.6m
SIZE OF PACKAGE	1600mm×360mm×180mm
LIFTING ROD WEIGHT	30kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg

MODEL	SMF957-S
LIGHT TYPE	Metal halide lamps
RATED POWER	1×1000W/2×1000W
LUMINOUS FLUX	1×105000Lm/2×105000Lm
RADIATION RANGE	The coverage radius can reach 100~200meters
LIGHT OPERATION LIFE	≥1YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
LIGHT PLATE SIZE	Φ1000×800mm(Size of expansion) Φ300×800mm (Size of storage)
WEIGHT OF LAMP PANEL	10kg
LIFTING MAST	
LIFTING METHOD	Hand lift and drop
LIGHTHOUSE TELESCOPIC	4.5M
CLOSED LENGTH	1.6m
SIZE OF PACKAGE	1600mm×360mm×180mm
LIFTING ROD WEIGHT	30kg
GENERATOR	
ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h
FULL LAMP CAR	
OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg



◎ SMF957-S



◎ SMF940
Hybrid oil electric
mobile lift work light

LIGHT PANEL

LIGHT TYPE	LED
RATED POWER	4×100W/4×200W(optional)
LUMINOUS FLUX	80000Lm/72000Lm
RADIATION RANGE	The coverage radius can reach50~150meters
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
WEIGHT OF LAMP PANEL	6kg

LIFTING MAST

BATTERY TYPE	Lead acid battery lithium battery(optional)
RATED CAPACITY	40Ah~100Ah
CHARGING TIME	≥12h
DISCHARGE TIME	≥6h
BATTERY WEIGHT	30kg~60kg

LIFTING MAST

LIFTING METHOD	Remote control automatic lifting
LIGHTHOUSE TELESCOPIC	4.5M/6m(optional)
CLOSED LENGTH	1.5m/1.8m
TIME OF RISE AND FALL	45S/35S
LIFTING ROD WEIGHT	6kg/12kg

GENERATOR

ENGINE TYPE	Gasoline generator/ diesel generator
VOLTAGE	AC220V/50Hz
RATED POWER	2KW/3KW/5KW/8KW/10KW
STARTING SYSTEM	Manual/electric start
FUEL TANK CAPACITY	10L~20L
CONTINUOUS OPERATING TIME	≥13h

FULL LAMP CAR

OPERATION CONTROL MODE	Remote and manual control
SHIPPING DIMENSION	1220mm×950mm×850mm
LAMP PROTECTION LEVEL	IP65
WIND RESISTANCE	6
BODY PROTECTION LEVEL	IP54
OPERATING WEIGHT	120Kg~180Kg

Light Tower (Trailer Type)

● SMF952-S

Trailer type mobile light tower(LED)



GENERATOR

ENGINE TYPE	DIESEL ENGINE
VOLTAGE	AC220V/50Hz
RATED POWER	7KW/8KW/10KW/12KW
STARTING SYSTEM	ELECTRIC START
FUEL TANK CAPACITY	50L
LUBRICATING OIL CAPACITY	1.65L/2.3L
CONTINUOUS OPERATING TIME	≥60h
NOISE LEVEL (7m)	80dB
NUMBER OF CYLINDERS	3/4
AIR INTAKE MODE	NATURAL ASPIRATED
RATED SPEED	1500r. p.m
COOLING SYSTEM	AIR-COOLED
FUEL CONSUMPTION (FULL LOAD)	1.66L
GENERATOR POLES/VOLTAGE	4P/230V/50Hz

LIGHT PANEL

LIGHT TYPE	METAL HALIDE LAMP/LED
RATED POWER	4×1000W/4×500W
LUMINOUS FLUX	4×90000Lm/4×50000Lm
RADIATION RANGE	2000~3000m ²
LIGHT OPERATION LIFE	GOLD HALOGEN LAMP:≥1 YEAR LED lights:≥3 YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
WEIGHT OF LAMP PANEL	42kg

LIFTING MAST

TYPE OF LIFT	Hydraulic pressure type
LIFTING HEIGHT/NUMBER OF KNOTS	9m/9
TIME OF RISE AND FALL	13S/25S
ANGLE OF ROTATION	Manual 360°
LIFTING ROD PACKAGE SIZE	2000×1600×1700mm

FULL LAMP CAR

MAX WORKING SIZE	2.3×2.4×9.1m
SHIPPING DIMENSION	1.6×1.5×2.3m
PACKING SIZE:	1.6×1.5×2.3m
WIND RESISTANCE	8
WHEEL	2×185/70R 13
FIXED BRACKET	4
AUXILIARY OUTPUT SOCKET	2×16Amp 1×32Amp 230V
OPERATING WEIGHT	910Kg (UNFUELED)

◎ SMF969A
Hydraulic lifting
mobile light tower



GENERATOR	
ENGINE TYPE	DIESEL ENGINE
VOLTAGE	AC220V/50Hz
RATED POWER	7KW/8KW/10KW/12KW
STARTING SYSTEM	ELECTRIC START
FUEL TANK CAPACITY	50L
LUBRICATING OIL CAPACITY	1.65L/2.3L
CONTINUOUS OPERATING TIME	≥60h
NOISE LEVEL (7m)	80dB
NUMBER OF CYLINDERS	3/4
AIR INTAKE MODE	NATURAL ASPIRATED
RATED SPEED	1500r. p.m
COOLING SYSTEM	AIR-COOLED
FUEL CONSUMPTION (FULL LOAD)	1.66L
GENERATOR POLES/VOLTAGE	4P/230V/50Hz
LIGHT PANEL	
LIGHT TYPE	METAL HALIDE LAMP/LED
RATED POWER	4×1000W/4×500W
LUMINOUS FLUX	4×90000Lm/4×50000Lm
RADIATION RANGE	2000~3000m ²
LIGHT OPERATION LIFE	GOLD HALOGEN LAMP:≥1 YEAR LED lights:≥3 YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
WEIGHT OF LAMP PANEL	42kg
LIFTING MAST	
TYPE OF LIFT	Hydraulic pressure type
LIFTING HEIGHT/NUMBER OF KNOTS	9m/9
TIME OF RISE AND FALL	13S/25S
ANGLE OF ROTATION	Manual 360°
LIFTING ROD PACKAGE SIZE	2000×1600×1700mm
FULL LAMP CAR	
MAX WORKING SIZE	2.3×2.4×9.1m
SHIPPING DIMENSION	1.6×1.5×2.3m
PACKING SIZE:	1.6×1.5×2.3m
WIND RESISTANCE	8
WHEEL	2×185/70R 13
FIXED BRACKET	4
AUXILIARY OUTPUT SOCKET	2×16Amp 1×32Amp 230V
OPERATING WEIGHT	910Kg (UNFUELED)

Light Tower (Trailer Type)

◎ SMF969B
Hydraulic lifting
mobile light tower



GENERATOR	
ENGINE TYPE	DIESEL ENGINE
VOLTAGE	AC220V/50Hz
RATED POWER	7KW/8KW/10KW/12KW
STARTING SYSTEM	ELECTRIC START
FUEL TANK CAPACITY	100L
LUBRICATING OIL CAPACITY	1.65L/2.3L
CONTINUOUS OPERATING TIME	≥60h
NOISE LEVEL (7m)	80dB
NUMBER OF CYLINDERS	3/4
AIR INTAKE MODE	NATURAL ASPIRATED
RATED SPEED	1500r. p.m
COOLING SYSTEM	AIR-COOLED
FUEL CONSUMPTION (FULL LOAD)	1.66L
GENERATOR POLES/VOLTAGE	4P/230V/50Hz
LIGHT PANEL	
LIGHT TYPE	METAL HALIDE LAMP/LED
RATED POWER	4×1000W/4×500W
LUMINOUS FLUX	4×90000Lm/4×50000Lm
RADIATION RANGE	2000~3000m ²
LIGHT OPERATION LIFE	GOLD HALOGEN LAMP:≥1 YEAR LED lights:≥3 YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
WEIGHT OF LAMP PANEL	42kg
LIFTING MAST	
TYPE OF LIFT	Hydraulic pressure type
LIFTING HEIGHT/NUMBER OF KNOTS	9m/9
TIME OF RISE AND FALL	13S/25S
ANGLE OF ROTATION	Manual 360°
LIFTING ROD PACKAGE SIZE	2000×1600×1700mm
FULL LAMP CAR	
MAX WORKING SIZE	2.3×2.4×9.1m
SHIPPING DIMENSION	2.3×1.3×2.5m
PACKING SIZE:	2.9×1.6×1.7m
WIND RESISTANCE	8
HEAVY DUTY SUPPORT FOOT	2×185/70R 13
FIXED BRACKET	4 hydraulic support feet
AUXILIARY OUTPUT SOCKET	2×16Amp 1×32Amp 230V
OPERATING WEIGHT	910Kg (UNFUELED)

- SMF970
Hydraulic lifting
mobile light tower



GENERATOR	
ENGINE TYPE	DIESEL ENGINE
VOLTAGE	AC220V/50Hz
RATED POWER	7KW/8KW/10KW/12KW
STARTING SYSTEM	ELECTRIC START
FUEL TANK CAPACITY	50L
LUBRICATING OIL CAPACITY	1.65L/2.3L
CONTINUOUS OPERATING TIME	≥70h
NOISE LEVEL (7m)	80dB
NUMBER OF CYLINDERS	3/4
AIR INTAKE MODE	NATURAL ASPIRATED
RATED SPEED	1500r. p.m
COOLING SYSTEM	AIR-COOLED
FUEL CONSUMPTION (FULL LOAD)	1.66L
GENERATOR POLES/VOLTAGE	4P/230V/50Hz
LIGHT PANEL	
LIGHT TYPE	METAL HALIDE LAMP/LED
RATED POWER	4×1000W/4×500W
LUMINOUS FLUX	4×105000Lm/4×50000Lm
RADIATION RANGE	2000~3000m ²
LIGHT OPERATION LIFE	GOLD HALOGEN LAMP:≥1 YEAR LED lights:≥3 YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
WEIGHT OF LAMP PANEL	30kg
LIFTING MAST	
LIFTING METHOD	Pneumatic lifting
LIGHTHOUSE TELESCOPIC	7.5m/9m(OPTIONAL)
CLOSED LENGTH	2m/2.8m
PACKING SIZE	300×320×3000mm
LIFTING ROD WEIGHT	25kg/40kg
FULL LAMP CAR	
MAX WORKING SIZE	2.8×2.8×9.1m
SHIPPING DIMENSION	1.6×1.5×2.0m
PACKING SIZE:	1.6×1.5×2.0m
WIND RESISTANCE	8
WHEEL	2
FIXED BRACKET	4
AUXILIARY OUTPUT SOCKET	2×16Amp.230V
OPERATING WEIGHT	830Kg (UNFUELED)

Light Tower (Trailer Type)

☉ SMF968A

Trailer type mobile light tower



GENERATOR

ENGINE TYPE	DIESEL ENGINE
VOLTAGE	AC220V/50Hz
RATED POWER	7KW/8KW/10KW/12KW
STARTING SYSTEM	ELECTRIC START
FUEL TANK CAPACITY	50L
LUBRICATING OIL CAPACITY	1.65L/2.3L
CONTINUOUS OPERATING TIME	≥70h
NOISE LEVEL (7m)	80dB
NUMBER OF CYLINDERS	3/4
AIR INTAKE MODE	NATURAL ASPIRATED
RATED SPEED	1500r. p.m
COOLING SYSTEM	AIR-COOLED
FUEL CONSUMPTION (FULL LOAD)	1.66L
GENERATOR POLES/VOLTAGE	4P/230V/50Hz

LIGHT PANEL

LIGHT TYPE	METAL HALIDE LAMP
RATED POWER	4×1000W/6×1000W
LUMINOUS FLUX	4×105000Lm/6×105000Lm
RADIATION RANGE	2000~3000m²
LIGHT OPERATION LIFE	GOLD HALOGEN LAMP:≥1 YEAR
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
WEIGHT OF LAMP PANEL	30kg

LIFTING MAST

LIFTING METHOD	HAND LIFT
LIGHTHOUSE TELESCOPIC	7M/9M(OPTIONAL)
CLOSED LENGTH	3.2m
PACKING SIZE	3600×320×120mm
LIFTING ROD WEIGHT	28kg

FULL LAMP CAR

MAX WORKING SIZE	2.8×2.8×9.1m
SHIPPING DIMENSION	1.6×1.5×2.0m
PACKING SIZE:	1.6×1.5×2.0m
WIND RESISTANCE	8
WHEEL	2
FIXED BRACKET	4
AUXILIARY OUTPUT SOCKET	2×16Amp.230V
OPERATING WEIGHT	650Kg (UNFUELED)

◎ SMF971
Solar mobile lifting
light tower



SOLAR PANEL

SOLAR PANEL POWER	2×300W/3×300W/4×300W(optional)
VOLTAGE	54V
CURRENT	8.18A
EXTENSION TYPE	MANUAL
NUMBERS OF SOLAR PANEL	2/3/4
SINGLE SOLAR PANEL SIZE	Length 1770 x width 1050mm

STORAGE BATTERY

TYPE	SOLAR ENERGY STORAGE VOLTAGE
VOLTAGE	12V
BATTERY CAPACITY	60Ah
STARTING CURRENT	60A
NUMBER OF BATTERY	1/2/3(optional)
EMERGENCY TIME	≥ 8 hours/≥ 12 hours/≥ 15 hours(optional)

LIGHT PANEL

LIGHT TYPE	LED
NUMBER OF LAMP HOLDERS	4/6
POWER OF ONE LIGHT	100W/150W/200W/300W(optional)
LUMINOUS FLUX	100lm/W
RADIATION RANGE	1000~2000m ²
ROTATION ANGLE OF LIGHT	HORIZONTAL 360°/VERTICAL 90°ADJUSTABLE
WEIGHT OF LAMP PANEL	30kg

LIFTING MAST

LIFTING METHOD	Pneumatic lifting
LIGHTHOUSE TELESCOPIC	7.5m/9m(optional)
CLOSED LENGTH	2m/2.8m
PACKING SIZE	300×320×3000mm
LIFTING ROD WEIGHT	25kg/40kg

FULL LAMP CAR

MAX WORKING SIZE	2.8×3.5×9.1m
SHIPPING DIMENSION	1.6×1.5×2.8m
PACKING SIZE:	1.6×1.5×2.0m
WIND RESISTANCE	8
WHEEL	2
FIXED BRACKET	4
AUXILIARY OUTPUT SOCKET	2×16Amp.230V
OPERATING WEIGHT	830Kg (UNFUELED)